

Corkline Rope Specifications for Corkline Rope

16 Carrier Impregnation: Resin		
Diameter Inch	5/8"	3/4"
Construction	16 Braid	16 Braid
Material	Polyester	Polyester
Wt kg/100 mtr	18.2	25.0
Wt lbs/600 feet	73.7	101.3
Breaking Stregnth Kgf	7000	9500
Breaking Stregnth Lbs	15400	20900

Corkline Rope Specifications for Corkline Rope

16 Carrier Impregnation: Tar		
Diameter Inch	5/8"	3/4"
Construction	16 Braid	16 Braid
Material	Polyester	Polyester
Wt kg/100 mtr	18.2	25.0
Wt lbs/600 feet	73.7	101.3
Breaking Stregnth Kgf	6000	8500
Breaking Stregnth Lbs	13200	18700

Maxiblend Float Hanging Line Specification for Maxiblend

8 Carrier Impregnation: Tar	
Diameter Inch	7/16"
Construction	8 Braid
Material	Polyester + PE
Wt kg/100 mtr	2.5
Wt lbs/600 feet	10.15
Breaking Stregnth Kgf	3200
Breaking Stregnth Lbs	7040



Garware-Wall Ropes Limited

Plot No. 11, Block D-1, MIDC, Chinchwad, Pune - 411 019 INDIA

Ph.: +91-20-30780000 Fax : 91-20-27473032

E-mail : exports@garwarewaropes.com Website : www.garwareropes.com