

12 Carrier Maxibraid Pelagic Ropes

Another specialty product developed by Garware Wall Ropes Limited for Pelagic application. Specialty resin and Wax treated for durability. Available in Stiff as well as soft lay variety.

Salient Features:

- ◆ 12 Braid balanced and round construction.
- ◆ Unique combination resin and wax treatment imparts durability and better abrasion resistance.
- ◆ Easy to Splice Rope.
- ◆ Retains stiffness even in wet condition.
- ◆ Reduced water absorption hence very little increase in the weight of the net. Thus reduced pulling force.
- ◆ Good strength retention even in wet condition vis-à-vis normal resin or wax coated nylon ropes.
- ◆ Controlled Elongation.
- ◆ Low and Uniform Shrinkage, ensuring consistent Net dimensions.

Rope Specifications:

Material of Construction : Nylon 6
 Type of Rope : 12 Strand Braided
 Treatment : Dual Resin
 Color : Off-White

Impregnated Specs			Water Retention	
Diameter	Wt/100ft	Breaking Strength	Time	Retention
Inch	Lbs	Lbs	Hrs	%
1/3"	3.65	5280	8	9
13/32"	4.51	6600	16	13
1/2"	5.75	8140	24	16
19/32"	7.23	11000		

Shrinkage			Elongation	
Method	Time	Shrinkage	Load	Elongation
	Min	%	%	%
Hot Air @ 100C	10	5-7	10	8
Boiling Water	10	9-11	20	14
Cold Water 23C	10	3-4	30	17

Garfil



Garware-Wall Ropes Limited

Plot No. 11, Block D-1, MIDC, Chinchwad, Pune - 411 019 INDIA
 Ph.: +91-20-30780000 Fax : 91-20-27473032

E-mail : exports@garwarewaropes.com Website : www.garwareropes.com